





## Commercial Class Current Transformers

WINDOW OPENING DIMENSION A	SERIES	MOUNTING STYLE	DIMENSIONS						CURRENT RATIO	ACCURACY AT 60 Hz	BURDEN VA AT 60 Hz								
			B	C	D	E	F	G											
1.13 (28.7)	CR2	RL	2.46 (62.5)	1.05 (26.7)					50:5	±3%	2.0								
		SFT							60:5	±2%	2.0								
		SFL							75:5	±2%	2.0								
		SHT							80:5	±2%	2.0								
		SHL							100:5	±1%	2.0								
									120:5	±1%	2.5								
									125:5	±1%	2.5								
									150:5	±1%	4.0								
									200:5	±1%	4.0								
									250:5	±1%	6.0								
	300:5	±1%	8.0																
1.56 (39.6)	CR5	RL	3.56 (90.4)	1.10 (27.9)					50:5	±2%	1.0								
		SFT							75:5	±2%	1.5								
		SFL							100:5	±2%	2.0								
		SHT							150:5	±1%	5.0								
		SHL							200:5	±1%	5.0								
		RT							250:5	±1%	10.0								
		RBT *							300:5	±1%	12.5								
		RBL *							400:5	±1%	12.5								
									500:5	±1%	20.0								
									600:5	±1%	25.0								
									750:5	±1%	25.0								
									800:5	±1%	25.0								
									1000:5	±1%	25.0								
									1200:5	±1%	30.0								
		2.50 (63.5)							CR7	RL	4.70 (919.4)	1.10 (27.4)					100:5	±2%	2.5
SFT	150:5		±1%	5.0															
SFL	200:5		±1%	5.0															
SHT	250:5		±1%	5.0															
SHL	300:5		±1%	12.0															
RT	400:5		±1%	15.0															
RBT	500:5		±1%	25.0															
RBL	600:5		±1%	30.0															
	750:5		±1%	30.0															
	800:5		±1%	35.0															
	1000:5		±1%	30.0															
	1200:5		±1%	35.0															
	1500:5		±1%	40.0															
	1600:5		±1%	45.0															
2.06 (52.3)	CR56		RL	3.50 (88.9)	1.09 (27.7)												50:5	±3%	0.5
		SFT	75:5						±1%		0.5								
		SFL	100:5						±1%		1.0								
		RT	150:5						±1%		2.5								
		RBT	200:5						±1%		4.0								
		RBL	250:5						±1%		6.0								
			300:5						±1%		7.5								
			400:5						±1%		10.0								
			500:5						±1%		12.5								
			600:5						±1%		15.0								
			750:5						±1%		7.0								
			800:5						±1%		8.0								
			1000:5						±1%		10.0								
			1200:5						±1%		12.5								
		3.00 (76.2)	CR76						RL		4.50 (114.3)	1.09 (27.7)					200:5	±1%	5.0
SFT	250:5			±1%	5.0														
SFL	300:5			±1%	6.0														
RT	400:5			±1%	10.0														
RBT	500:5			±1%	10.0														
RBL	600:5			±1%	10.0														
	750:5			±1%	10.0														
	800:5			±1%	12.5														
	1000:5			±1%	10.0														
	1200:5			±1%	10.0														
	1500:5			±1%	12.5														
	1600:5			±1%	12.5														
	2000:5			±1%	15.0														
.64 (16.3)	CR1A			RL	1.99 (50.5)	1.25 (31.8)											50:5	±2%	1.0
																	60:5	±1%	2.0
			75:5	±1%							2.0								
			80:5	±1%							2.0								
			100:5	±1%							2.5								
			120:5	±1%							3.0								
			125:5	±1%							3.0								
			150:5	±1%							4.0								
			200:5	±1%							5.0								
			250:5	±1%							7.5								

\* RBT and RBL mounting styles in the CR5 series are not available in current ratios of 750:5 thru 1200:5



